

THE MASON TIMBER

RANGE AND RELIABILITY



THE MATE RANGE MASON TIMBER

RANGE AND RELIABILITY



CONTENTS

THE MATE RANGE	6	BRANDED HEXAGON	12
The Range	6	LOCKING NUTS	
The Quality	6	Philidas Industrial Nut	12
The Value	6	Philidas Turret Nut	12
The Support	6	Philidas Mark V Nut	12
The Packaging	7	Binx Self Locking Nut	12
The Labelling	7	Stover Self Locking Nut	12
The 'Extended' Range	7		
BOLTING	9	WASHERS	13
	-	Plain Washer Form A	13
Hexagon Head Bolt 8.8 Fine Pitch	9 9	Plain Washer Form B	13
Hexagon Head Bolt 8.8 Fine Pitch Hexagon Head Bolt 10.9	9	Plain Washer Form C	13
нехадоп неаа вой 10.9 Hexagon Head Setscrew 8.8	9	Plain Washer T3	13
Hexagon Head Setscrew 8.8 Fine Pitch	9	Plain Washer T4	13
Hexagon Head Setscrew 10.9	9	Square Section Spring Washer	13
Assembled Bolting	9	Rectangular Section Spring Washer	13
Cup Square Hexagon Bolt & Nut	9	Repair Washer	13
cap square rickagori boli a rvat		Internal Shakeproof Washer	14
ALL TUDEAD	•	External Shakeproof Washer	14
ALL THREAD	9	Square Plate Washer	14
All Thread	9	Starlock Washer	14
All Thread Left Hand	10	Black Mild Steel Washer Form G	14 14
All Thread Fine Pitch	10	Crinkle Washer Through Hardened Washer Grade 10	14 14
All Thread 8.8	10	Red Fibre Washer	14
HEXAGON SOCKET SCREWS	10	MACHINE SCREWS	14
Hexagon Socket Cap Screw	10		17
Hexagon Socket Dome Screw	10	Slotted Countersunk Machine Screw	14
Hexagon Socket Countersunk Screw	10	Slotted Pan Head Machine Screw	14
Hexagon Socket Shoulder Screw	10	Slotted Cheese Head Machine Screw	15
Hexagon Socket Setscrew	10	Pozi Countersunk Machine Screw	15
Hexagon Socket Dome Flange Screw	10	Pozi Pan Head Machine Screw	15
HEXAGON NUTS	11	SELF TAPPING SCREWS	15
	11	Pozi Countersunk Self Tapping Screw (AB)	15
Hexagon Full Nut Hexagon Lock Nut	11	Pozi Pan Head Self Tapping Screw (AB)	15
Hexagon Nylon Insert Nut Type P	11	Pozi Flange Head Self Tapping Screw (AB)	15
Hexagon Nylon Insert Nut Type T	11	Hexagon Head Self Drilling Self Tapping Screw	
Hexagon Plain Flange Nut	11		
Hexagon Serrated Flange Nut	11	RIVETS	16
Hexagon Weld Nut	11	UIACIS	10
Hexagon Connecting Nut	11	Multi Grip Rivet	16
Hexagon Dome Nut	11	Sealed (Cap) Rivet	16
Pronged Tee Nut	12	Dome Rivet	16
Wing Nut	12	Countersunk Rivet	16
Hexagon Castle Nut	12	Flange Rivet	16
Hexagon Slotted Nut	12	Peel Rivet	16
Bright Mild Steel Hexagon Full Nut	12	Dome Head Rivet Nut	16
Bright Mild Steel Hexagon Full Nut Left Hand	12	Countersunk Head Rivet Nut	16
Bright Mild Steel Hexagon Lock Nut	12	Small Head Rivet Nut	16
Bright Mild Steel Hexagon Lock Nut Left Hand	12		

SELF DRILLING SCREW	16	SLEEVE, SHIELD, DROP IN	19	WOODSCREWS	23
Drill Screw	16	WEDGE ANCHORS		Pozi Double Countersunk	23
Composite Panel Screw	16	Hexagon Nut Sleeve Anchor	19	Twin Thread Woodscrew	
Countersunk Screw	16	Hexagon Loose Bolt Sleeve Anchor	19	Pozi Round Head Twin Thread Woodscrew	23
		Countersunk Head Loose Bolt Sleeve Anchor	19	Pozi Countersunk Carcass Screw	23
ROOFING	17	Loose Bolt Shield Anchor	19	Pozi Double Countersunk	23
		Projecting Shield Anchor	19	Single Thread Woodscrew	
Selawasher	17	Hook Bolt Shield Anchor	20	Clutch Head Twin Thread Woodscrew	23
Roofing Bolt & Square Nuts	17	Eye Bolt Shield Anchor	20	Slotted Round Brass Woodscrew	23
Hook Bolt	17	Śhield Anchor (Shield Only)	20	Slotted Countersunk Brass Woodscrew	23
		Plain Drop In Wedge Anchor	20		
LIFTING & CLAMPING	17	Lipped Drop In Wedge Anchor	20	DRY WALL SCREWS	23
Dynamo Eyebolt	17			Phillips Recess Bugle Head Drywall Screw	23
Collared Eyebolt	17	MASONRY NAILS	20	Phillips Recess Pan Head Drywall Screw	23
Eyenut	17	& SCREWBOLTS		Phillips Recess Wafer Head Drywall Screw	23
Wire Rope Grip	17			Drywall Nail	23
D Shackle	17	Masonry Nails	20	-, -	
U Bolt + 2 Nuts	17	Hexagon Concrete Screwbolt	20	OOAGUEODEWE	0.4
O BOIL 1 2 Ndt3	17	Hexagon Flange Concrete Screwbolt	20	COACHSCREWS	24
DINO	4-7	Countersunk Torx Concrete Screwbolt	20	Hexagon Head Coachscrew	24
PINS	17	Hexagon Head Screwbolt	20	riesagon rieda eoderiseren	
Dowel Pin	17	Socket Countersunk Screwbolt	20	OADO O COUEDO	
Hardened & Ground Dowel Pin	17	Eye Screwbolt	20	CAPS & COVERS	24
Extractable Dowel Pin	17	Hook Screwbolt	20	Surface Screw Cup	24
Spring Tension (Sellok Pins)	18	Scaffold Bolt	20	Pozi Screw Cover Cup	24
Cotter Pin	18			Turned Pattern Screw Cup	24
Cotte. 7 m	, 0	CHEMICAL RESINS	21	ramea rattem serem cup	- '
LINDAPTER	18	ETA Approved Chemical Resins	21	NAILS	24
	10	Chemical Resin Guns	21	ITAILU	47
Support & Cavity Fixings	18	Chemical Resin Accessories	21	Round Wire Nail	24
Decking & Floor Fixings	18	ETA Approved Spin In Capsules	21	Round Lost Nail	24
Steelwork & Rail Fixings	18	Hammer In Capsules	21	Annular Ring Shank Nail	24
		Studs	21	Clout Head Nail	24
MISCELLANEOUS	18	Internal Threaded Sockets	21	Extra Large Clout Head Nail	24
		memai medaca societs	21	Brudaw Alloy Dowel	24
Terry Hose Clips Jubilee Hose Clips	18 18	LIGHT DUTY FIXINGS	21		
Hexagon Hank Rivet Bush	18			THE TITE RANGE	25
Round Serrated River Bush	18	Frame Fixing	21		
nouria scriatca niver basir	70	Hammer Fixing	21	STAINLESS STEEL RANGE	27
		Window Frame Anchor	21	STAINLESS STEEL HANGE	21
THROUGH BOLTS	19	Concrete Screw	22	BRASS & NYLON RANGE	31
Through Bolts	19	OAWITY FIVINGS	00	DNASS & NILUN NANUE	JΙ
ETA Approved Through Bolts	19	CAVITY FIXINGS	22		
		Hollow Wall Anchor	22	CERTIFIED RANGE	34
HEAVY DUTY ANCHORS	19	Plasterboard Fixings	22		
		Spring Toggle & Screw	22	TECHNICAL INFORMATION	20
ETA Approved Countersunk	19	Wall Plugs	22	TECHNICAL INFORMATION	38
Heavy Duty Anchor	40	Ţ.			
ETA Approved Heavy Duty	19	CABLE TIES	22	FIXINGS SELECTION CHART	45
Anchor Hexagon Bolt	10	CADLE HES	22	· ····································	. •
ETA Approved Heavy Duty Anchor Stud	19	Cable Ties	22		



Introducing the Mates range of fasteners, screws and fixings: Reliability in every application.

The Range:

METAL MATE

MetalMate® fasteners for engineering, construction, production, repair and maintenance.



MasonMate® fixings for work in all types of masonry, stone and brick.



TimberMate® screws for all timber related applications.

The Quality:

The 3 Mate brands have all, or some, of the following quality characteristics:

- Manufactured by worlds class producers.
- Manufactured by suppliers adhering to the quality management requirements of ISO 9001:2008 and also ISO/TS 16949:2009.
- Full product traceability to the original raw material.
- EN: ISO 10204 3.1 certification.
- CE approval and marking.
- ETA approval.
- CR3 ROHS (Restriction of use of Hazardous Substances) compliance.
- Independently tested to recognised standards.

The Value:

Performance, consistency and reliability does not come cheaply but the Mates range will always offer reassuring value for money and is proudly market competitive.

The Support:

Available through your local distributor who has immediate access to:

- Technical support
- Technical specifications
- Product testing support
- Mobile load testing and hardness testing equipment
- On-site support
- Next day delivery
- Catalogues and wall charts
- Marketing material

The Packaging:

- Strong, clearly labelled and distinctive 'no nonsense' packaging.
- All branded with the Mates logo.
- Packaging options:
- Fully branded 'inner' boxes.
- Manufacturers outer cartons containing multiple inner boxes.
- Manufacturers outers containing loose product.
- Manufacturers single item pallets made up of multiple outer cartons.



The Labelling:

Full Traceability

Quality assured back to trusted & audited factories and the raw material batch

Nothing To Hide!

A name we are proud of

Quantity

QR Code

To be scanned for product datasheet

Everything You Need To Know

What's in the box/grade/material/specification/size/finish/drive

H&C Product Code

For easy reference

The 'Extended' Range of market leading brands



Tite® Range for unique innovation and design when working in all types of timber and masonry.



UK manufacturers of innovative connection systems for all steel work.



European manufactured quality blind rivet system.



UK manufactured the original high quality 'screwbolt' anchor offering exceptional strength for permanent and temporary applications in all substrates.



Qty: 100

5 050420 017626

*FASTENERS

Hexagon

Full Nut / M12

DIN 934 Class 8

Zinc & Clear CR3

Code: **Z0322M58**

UK designed all metal locking nuts.



European manufactured system of standard anchors for small to large applications carrying ETA accreditation.



Manufactured in the UK and the original hose clamp now offering a wide range of clamping solutions.

THE FULL RANGE **RANGE AND RELIABILITY**



DIN 931



Hexagon Head Bolt 8.8

Self Colour Zinc Plated Hot Dipped Galvanised Sizes available from: Diameter: M4 to M56 Length: 8mm to 600mm



DIN 931

Hexagon Head Bolt 8.8 Fine Pitch

Self Colour

Sizes available from: Diameter: M10 to M24 Length: 40mm to 200mm



DIN 960

Hexagon Head Bolt 10.9

Self Colour Zinc Plated

Sizes available from: Diameter: M6 to M56 Length: 30mm to 760mm





Hexagon Head Bolt (Non-Ferrous)

A2 Stainless Steel Sizes available from: Diameter: M6 to M24 Length: 25mm to 150mm



Hexagon Head Setscrew 8.8 Self Colour

Zinc Plated Hot Dipped Galvanised

Sizes available from: Diameter: M3 to M48 Lenath: 6mm to 400mm



DIN 933

Hexagon Head Setscrew 8.8 Fine Pitch

Self Colour

Sizes available from: Diameter: M8 to M24 Length: 16mm to 100mm



DIN 961



DIN 933



Hexagon Head Setscrew 10.9 DIN 933

Self Colour Zinc Plated

Sizes available from: Diameter: M5 to M36 Length: 10mm to 200mm



Hexagon Head Setscrew (Non-Ferrous)

A2 Stainless Steel A4 Stainless Steel

Sizes available from: Diameter: M3 to M24 Length: 6mm to 200mm

METAL

DIN 603/555

CE

DIN 933

Hexagon Head Setscrew (Nylon)

Nvlon

Sizes available from: Diameter: M5 to M16 Lenath: 20mm to 55mm

METAL

DIN 603



Assembled Bolting 8.8 EN: 15048-1:2007

7inc Plated Hot Dipped Galvanised Sizes available from: Diameter: M12 to M24 Length: 30mm to 90mm



META

Cup Square Hexagon Bolt & Nut 4.8

Zinc Plated Hot Dipped Galvanised Sizes available from: Diameter: M6 to M20

Length: 16mm to 400mm

ALL ZINC PLATED LENGTHS UPTO 150MM ARE **FULLY THREADE**



METAI

Cup Square Hexagon Bolt & Nut (Non-Ferrous)

A2 Stainless Steel Sizes available from: Diameter: M6 to M10

Length: 16mm to 150mm

METAL



ALL THREAD



All Thread

Mild Steel All Thread

Self Colour Zinc Plated

Sizes available from:

Diameter: M3 to M48 Length: 300mm to 3mtr

UNC / UNF / BSW / BSF SIZING ALSO AVAILABLE



All Thread (Non-Ferrous)

A2 Stainless Steel A4 Stainless Steel

Sizes available from: Diameter: M3 to M30 Length: 300mm to 3mtr

METAI



All Thread (Nylon)

Nvlon Sizes available from:

Diameter: M6 to M12 Length: 1mtr







All Thread Left Hand Mild Steel All Thread Self Colour Sizes available from: Diameter: M8 to M24 Lenath: 1mtr



All Thread Fine Pitch Mild Steel All Thread Self Colour Sizes available from: Pitch: 1.0 / 1.25 / 1.5 / 2.0 Diameter: M10 to M24 Length: 1mtr METAL



All Thread 8.8 Self Colour Galvanised Zinc Plated Sizes available from: Diameter: M6 to M30 Lenath: 1mtr to 3mtr



HEXAGON SOCKET SCREWS



Hexagon Socket Cap Screw 12.9

Self Colour Zinc Plated Sizes available from: Diameter: M2 to M48



ISO: 7380

METAI

METAL

ISO: 7379

DIN 912

METAL

Hexagon Socket Cap Screw (Non-Ferrous)

A2 Stainless Steel Sizes available from: Diameter: M2.5 to M16 Length: 6mm to 160mm



Hexagon Socket Dome Screw 10.9

Zinc Plated Sizes available from: Diameter: M3 to M16 Lenath: 5mm to 120mm



ISO: 7380



Hexagon Socket Dome Screw (Non-Ferrous)

A2 Stainless Steel Sizes available from: Diameter: M3 to M12 Length: 6mm to 80mm



Hexagon Socket Countersunk Screw 10.9

Self Colour Zinc Plated Sizes available from: Diameter: M3 to M24 Length: 6mm to 200mm



DIN 7991

DIN 912

METAL

Hexagon Socket Countersunk Screw (Non-Ferrous) A2 Stainless Steel

Sizes available from: Diameter: M3 to M16 Length: 6mm to 100mm



DIN 916



Hexagon Socket Shoulder Screw 12.9

Self Colour Sizes available from: Diameter: M6 to M16 Length: 10mm to 100mm



Hexagon Socket Setscrew 14.9

Self Colour Zinc Plated Sizes available from: Diameter: M2 to M24 Lenath: 2mm to 60mm DIN 916

METAI

Hexagon Socket Setscrew (Non-Ferrous)

A2 Stainless Steel Sizes available from: Diameter: M3 to M12 Length: 2mm to 60mm



Hexagon Socket Dome Flange Screw 10.9


Zinc Plated Sizes available from: Diameter: M3 to M10 Length: 6mm to 50mm



YFS METAI

RANGE AND RELIABILITY

MetalMate® socket caps, countersunk and dome screws are all manufactured by the worlds leading producer. Fang Sheng, and carry the famous YFS head marking.



HEXAGON NUTS







Hexagon Full Nut Grade 10 Self Colour Zinc Plated Sizes available from:

Diameter: M6 to M52



DIN 439B

METAL

DIN 934

A2 Stainless Steel A4 Stainless Steel Sizes available from: Diameter: M2 to M30

(Non-Ferrous)

Hexagon Full Nut



METAL

DIN 439B



UNC / UNF SIZING ALSO AVAILABLE




Hexagon Lock Nut Grade 4 Self Colour Zinc Plated Sizes available from:

(Non-Ferrous) Brass A2 Stainless Steel Sizes available from: Diameter: M4 to M20

Hexagon Lock Nut

METAL





DIN 934







Hexagon Plain DIN 6923 Flange Nut Class 8 Zinc Plated Sizes available from: Diameter: M4 to M12 METAI













BS 3692



Pronged Tee Nut

Self Colour Zinc Plated Sizes available from: Diameter: M4 to M10



METAL

METAL

METAL

BS 3692

BS 3692

Wing Nut

Zinc Plated A2 Stainless Steel Sizes available from:

Diameter: M5 to M16



ANSI: B18.17

METAL

METAL

BS 3692

BS 3692

Hexagon Castle Nut

Self Colour



Sizes available from: Diameter: M6 to M48

METAL

BS 3692



Hexagon Slotted Nut

Self Colour

Sizes available from: Diameter: M10 to M36



Bright Mild Steel Hexagon Full Nut Grade 4

Self Colour

Sizes available from: Diameter: M6 to M42



Bright Mild Steel Hexagon Left Hand Full Nut Grade 4

Self Colour Sizes available from:

Diameter: M6 to M30

METAL



Bright Mild Steel Hexagon Lock Nut Grade 4

Self Colour

Sizes available from: Diameter: M8 to M48



Bright Mild Steel Hexagon Left Hand Lock Nut Grade 4

Self Colour

Sizes available from: Diameter: M10 to M20

METAL

RANGE AND RELIABILITY

Are you sure your DIN 934 are class 8?

MetalMate® DIN 934 nuts are independently tested to ensure they are true class 8.

BRANDED HEXAGON LOCKING NUTS



Philidas Industrial Nut Grade 8

Self Colour 7inc & Yellow Sizes available from: Diameter: M5 to M36



Philidas Turret Nut Grade 8

7inc & Yellow

Sizes available from: Diameter: M4 to M30



Philidas Mark V Nut Grade 8

7inc & Yellow Sizes available from: Diameter: M4 to M20



Binx Self Locking Nut Grade 4

Zinc Plated Sizes available from:





Stover Self Locking Nut

Class 8 Zinc Plated

Sizes available from: Diameter: M6 to M24



DIN 980V

RANGE AND RELIABILITY

Philidas and Binx perfectly compliment the extensive Mate range of hexagon nuts.















DIN 6798



Internal Shakeproof Washer

Sizes available from:



DIN 6798

BS 3410

Internal Shakeproof Washer (Non-Ferrous)

A2 Stainless Steel Sizes available from: Diameter: 4mm to 24mm



External Shakeproof Washer

Zinc Plated

Sizes available from: Diameter: 3mm to 24mm



BS 4320



Square Plate Washer

Zinc Plated Sizes available from:



Starlock Washer

Capped / Uncapped Sizes available from: Diameter: 2mm to 24mm



Black Mild Steel Washer

Form G

Self Colour Zinc Plated Galvanised

Sizes available from: Diameter: 5mm to 30mm

METAL





METAL

DIN 6916

DIN 6798

METAL







Sizes available from: Diameter: 12mm to 24mm

METAL

Red Fibre Washer

Self Colour

Sizes available from: Diameter: 2.5mm to 16mm



DIN 963

RANGE AND RELIABILITY

METAL

MetalMate® plain washers form A have a hardness of between 140hv and 250hv ensuring performance and reliability.

MACHINE SCREWS



Slotted Countersunk Machine Screw

Sizes available from: Diameter: M3 to M12 Length: 6mm to 100mm



Slotted Countersunk Machine Screw (Non-Ferrous)

A2 Stainless Steel Brass Sizes available from: Diameter: M3 to M10 Length: 6mm to 100mm

DIN 963

Slotted Pan Head Machine Screw

Zinc Plated Sizes available from: Diameter: M3 to M8 Length: 5mm to 70mm

DIN 85



















The MetalMate® range of machine screws, sheet metal screws and fasteners are designed to meet the needs of the more discerning distributors.

RANGE AND RELIABILITY

SELF TAPPING SCREWS

















Multi Grip Vibrations free, wide range of grip

Multi Grip Rivet

Aluminium Zinc Plated Steel

Sizes available from: Diameter: 3.2mm to 4.8mm

SARIV



retention, pressure and water-tightness

Sealed (Cap) Rivet

Aluminium

Sizes available from:

Diameter: 3.2mm to 4.8mm

SARIV



Standard low-profile most applications

Dome Rivet

Copper Aluminium Zinc Plated Steel Stainless Steel

Sizes available from:

Diameter: 2.4mm to 6.4mm head, suitable for

SARIV



120° head desian. Used wherever a flush surface is required

Countersunk Rivet

Aluminium Zinc Plated Steel Stainless Steel

Sizes available from:

Diameter: 3.2mm to 4.8mm

SARIV



For use where thin, rittle, soft, or vulnerable materials are fastened. Provides large bearing ırface on primary side, deal for covering enlarge

Flange Rivet

Aluminium

Sizes available from:

Diameter: 3.2mm to 4.8mm

SARIV



Suitable for

ioinina plastics. rubber wood and laminates tolerance of over-sized holes **Peel Rivet**

Aluminium Sizes available from:

Diameter: 4mm to 4.8mm

SARIV



Dome Head Rivet Nut

Aluminium Steel

A2 Stainless Steel

Sizes available from:

Diameter: M4 to M10

SARIV



Countersunk Head Rivet Nut

Sizes available from:

Diameter: M4 to M8

SARIV



Small Head Rivet Nut

Sizes available from:

Diameter: M4 to M10

SARIV

SELF DRILLING SCREWS



Drill Screw

Light Section Drill Screw

Zinc Plated

Sizes available from:

Diameter: 5.5mm

Length: 25mm to 100mm

METAL MATE



Drill Screw

Heavy Section Drill Screw

Zinc & Yellow

Sizes available from:

Diameter: 5.5mm

Length: 25mm to 100mm

METAL



Composite Panel Screw

Light Section Composite Panel Screw

Zinc & Yellow

Sizes available from:

Diameter: 5.5mm

Length: 76mm to 120mm



Composite Panel Screw

Heavy Section Composite Panel Screw

Zinc & Yellow

Sizes available from:

Diameter: 6.3mm

Lenath: 60mm to 125mm



Countersunk Screw

Liaht

Zinc Plated

Sizes available from:

Diameter: 4.8mm to 5.5mm Lenath: 25mm to 110mm



Countersunk Screw

Heavy

Zinc Plated

Sizes available from:

Diameter: 5.5mm Lenath: 60mm to 110mm

ROOFING





Selawasher

Black Clear

Sizes available from: 1D: 6mm & 8mm 6D: 20mm & 28mm





Roofing Bolt & Square Nuts

Zinc Plated

Sizes available from: Diameter: M5 to M10 Length: 8mm to 180mm





Hook Bolt

Zinc & Yellow

Sizes available from:

Diameter: **M6** to **M8**Length: **60mm** to **220mm**



LIFTING & CLAMPING



Dynamo Eyebolt

Self Colour

Sizes available from:
Diameter: M6 to M24





Collared Eyebolt

Self Colour

Sizes available from: Diameter: M6 to M24





lf Colour

Sizes available from: Diameter: M10 to M16





Wire Rope Grip

Galvanised

Sizes available from:

Diameter: 1/8" to 3/4"





D Shackle

Galvanised

Sizes available from:
Diameter: 3/16" to 3/4"

METAL. MATE



U Bolt + 2 Nuts

Zinc Plated

Sizes available from:

Diameter: M8 to M16 Length: 15mm to 150mm

METAL.

PINS



Dowel Pin

Silver Steel

Sizes available from:
Diameter: 3mm
Length: 10mm to 25mm

METAL



Hardened & Ground Dowel Pin

Self Colour

Sizes available from:
Diameter: 4mm to 16mm
Length: 10mm to 100mm

MATE



Extractable Dowel Pin

Self Colour

Sizes available from:
Diameter: 6mm to 16mm
Length: 20mm to 80mm

METAL. MATE





Spring Tension (Sellok Pins)

Self Colour

Sizes available from:

Diameter: M1.5 to M12 Length: 6mm to 100mm





Cotter Pin

Self Colour

Sizes available from:

Diameter: M2 to M8 Length: 16mm to 100mm



BS 1574

RANGE AND RELIABILITY

The Mates range reaches parts of the fastener market ignored by others. A full offering of pins, keys, collars, lifting and clamping products available next day.

LINDAPTER



Support & Cavity Fixings

Type FL Clamp Type FLS Clamp Type HC Hemispherical Cups Type HW Hemispherical Washers Type LC Lindiclip Type SW Swivel Assembly Type WF Webfix

lindapter⁶

Hollo-Bolts

Lindiholts



Decking & Floor Fixings

Type AW Alphawedge Type MF Type MW2 Multiwedge Type SD2 Slimdeck Type TC Toggle Clamp Type TR60 Wedge Fixing Type VN Vee Nut

Type FF Floorfast Type GF Grate-Fast

[indapter

Steelwork & Rail Fixings

Type A Clamp Type AF Clamp Type AFCW Packing Type AFW Adaptor Washer Type B Clamp Type BSLN Long Nose Type CF High Slip Resistance Clamp Type P2 Packing

Type F9 Flange Clamp Type FC Flush Clamp Type LR Self Ádjusting Clamp Type P1 Packing Type BR Rail Clip

(indapter

Type D2 Adjustable Clamp

MISCELLANEOUS

U-Bolts



Terry Hose Clips

Zinc Plated

Sizes available from: 9.5mm to 305mm





Terry Hose Clips (Non-Ferrous)

Stainless Steel

Sizes available from: 8mm to 140mm





Jubilee Hose Clips

Type CW Clipped Washer

...& Many More

Zinc Plated

Sizes available from: 9.5mm to 318mm





Jubilee Hose Clips (Non-Ferrous)

Stainless Steel Sizes available from: 9.5mm to 318mm



Hexagon Hank Rivet Bush

Self Colour Zinc Plated

Sizes available from: Diameter: M3 to M10 Length: **10G** to **20G**



Round Serrated Hank Rivet Bush

Self Colour Zinc Plated

Sizes available from: Diameter: M3 to M10 Length: **10G** to **18G**



THROUGH BOLTS





Through Bolt
Zinc Plated
Hot Dipped Galvanised
Sizes available from:
Diameter: M6 to M24
Length: 50mm to 300mm



ETA Approved Through Bolt
Zinc Plated
Sizes available from:
Diameter: M8 to M20
Length: 60mm to 220mm



(NC)
A4 St
Sizes
Dian
Leng

ETA Approved Through Bolt (Non-Ferrous)

A4 Stainless Steel

Sizes available from:
Diameter: M8 to M20
Length: 60mm to 220mm



HEAVY DUTY ANCHORS



ETA Approved Countersunk Heavy Duty Anchor

Zinc Plated

Sizes available from:
Diameter: 6mm to 12mm
Length: 10mm to 40mm



MASON

MATE




ETA Approved Heavy Duty Anchor Hexagon Bolt

Zinc Plated

Sizes available from:
Diameter: 12mm to 28mm
Length: 80mm to 185mm





ETA Approved Heavy Duty Anchor Stud

Zinc Plated

Sizes available from:
Diameter: 8mm to 16mm
Lenath: 10mm to 70mm



M

SLEEVE, SHIELD & DROP IN WEDGE ANCHORS



Hexagon Nut Sleeve Anchor

Zinc & Yellow

Sizes available from:
Diameter: 6mm to 20mm
Length: 18mm to 151mm





Hexagon Nut Sleeve Anchor (Non-Ferrous)

A4 Stainless Steel

Sizes available from:
Diameter: 6mm to 20mm
Length: 18mm to 151mm





Hexagon Loose Bolt Sleeve Anchor

Zinc & Yellow

Sizes available from:
Diameter: 6mm to 20mm
Lenath: 18mm to 151mm

MASON MATE



Countersunk Head Loose Bolt Sleeve Anchor

Zinc & Yellow

Sizes available from:
Diameter: 6mm to 20mm
Length: 18mm to 151mm





Loose Bolt Shield Anchor

Zinc & Yellow

Sizes available from:
Diameter: 6mm to 16mm
Length: 10mm to 75mm

MASON



Projecting Shield Anchor

Zinc & Yellow

Sizes available from:
Diameter: 6mm to 16mm
Length: 10mm to 75mm

MASON_®





Hook Bolt Shield Anchor

Zinc & Yellow Sizes available from: Diameter: 6mm to 12mm Length: 45mm to 75mm





Eye Bolt Shield Anchor

Zinc & Yellow Sizes available from: Diameter: 6mm to 12mm Length: 45mm to 75mm





Shield Anchor (Shield Only)

Zinc & Yellow Sizes available from: Diameter: 6mm to 12mm Length: 45mm to 75mm





Plain Drop In Wedge Anchor

Zinc & Yellow Sizes available from: Diameter: M6 to M20





Plain Drop In Wedge Anchor (Non-Ferrous)

A4 Stainless Steel Sizes available from: Diameter: M6 to M16

MASON




Lipped Drop In Wedge Anchor

Zinc & Yellow Sizes available from: Diameter: M8 & M12

MASON

MASONRY NAILS & SCREWBOLTS



Masonry Nails

Countersunk

Zinc Plated

Round

Zinc Plated

Sizes available from:

Diameter: 2.5mm to 3.5mm Length: 25mm to 100mm

MASON



Hexagon Concrete Screwbolt

7inc & Yellow

Sizes available from:

Diameter: 8mm to 12mm Length: 60mm to 200mm



Hexagon Flange 7inc & Yellow


Concrete Screwbolt

Sizes available from:

Diameter: 6mm

Length: 50mm to 100mm

SER



Countersunk Torx Concrete Screwbolt

7inc & Yellow

Sizes available from:

Diameter: 6mm Lenath: 50mm to 100mm





Hexagon Head Screwbolt

Zinc & Yellow

Sizes available from:

Diameter: M6 to M20 Length: 30mm to 200mm



Socket Countersunk Screwbolt

Zinc & Yellow

Sizes available from:

Diameter: M6 to M12 Length: 50mm to 150mm





Eye Screwbolt

Zinc & Yellow Sizes available from: Diameter: 8mm to 12mm





Hook Screwbolt

Zinc & Yellow Sizes available from:

Diameter: 10mm & 12mm Length: **65mm** & **75mm**





Scaffold Bolt

Zinc & Yellow Sizes available from: Diameter: 12mm Length: 185mm







Styrene Free Polyester Resin

Sizes available: Size: 165ml & 300ml



Styrene Free Epoxy Acrylate

Sizes available: Size: **410ml**



High-Load Vinylester Resin

Sizes available: Size: 410ml











Chemical Resin Guns

Light Duty Heavy Duty C4 Heavy Duty



Chemical Resin Accessories

Mixer Nozzles Hole Cleanina Brushes Blow Out Pumps Wire Mesh Sleeves Nylon Sleeves

MASON



ETA Approved Spin In Capsules

Sizes available from:

Diameter: 8mm to 20mm





Hammer In Capsules



MASON

Studs

Zinc & Yellow

Hot Dipped Galvanised

Sizes available from:

Diameter: M8 to M24 Length: 110mm to 300mm

MASON



MASON



Internal Threaded Sockets

7inc Plated

Sizes available from: Diameter: M8 to M16

MASON



Internal Threaded Sockets (Non-Ferrous)

A2 Stainless Steel

Sizes available from:

Diameter: M8 to M16

MASON

LIGHT DUTY FIXINGS



Frame Fixing

Nvlon - Zinc & Yellow Screw Sizes available from: Diameter: 8mm & 10mm Length: 60mm to 160mm

MASON



Hammer Fixing

Nvlon - Zinc & Yellow Screw Nvlon - Stainless Steel Screw

Sizes available from:

Diameter: 5mm to 8mm Length: 30mm to 135mm

MASON



Window Frame Anchor

Nvlon / Steel

Sizes available from:

Diameter: 8mm & 10mm Length: **75mm** to **165mm**







Concrete Screw

Zinc & Yellow

Sizes available from:

Diameter: **7.5mm** Length: **60mm** to **150mm**

MASON MATE

RANGE AND RELIABILITY

MASON MATE The MasonMate® range is supported by our in-house technical advisors and on-site 'pull-out' testing equipment.

CAVITY FIXINGS



Hollow Wall Anchor

Zinc Plated

Sizes available from:
Diameter: 4mm to 6mm
Length: 20mm to 65mm

ANCHOR SETTING TOOL ALSO AVAILABLE

MASON MATE



Plasterboard Fixings

Metal

Sizes available from:
Diameter: 4.5mm
Length: 30mm to 45mm

MASON MATE



Plasterboard Fixings (Nylon)

Nylon Sizes available from: Diameter: 4.5mm Length: 30mm to 45mm

MASON



Spring Toggle & Screw

Zinc Plated

Sizes available from:

Diameter: **3mm** to **6mm** Lenath: **50mm** to **100mm**

SPRING TOGGLE WINGS ONLY ALSO AVAILABLE

MASON_®



Plastic Wall Plugs

Colours available in: Brown: 7mm x 37mm Red: 6mm x 30mm Yellow: 5mm x 25mm Blue: 10mm x 50mm

> MASON MATE



Nylon Wall Plugs

Type E - Nylon / Grey
Type TPF - Nylon / Grey
Sizes available from:
Diameter: 5mm to 14mm
Length: 25mm to 75mm

MASON MATE

CABLE TIES



Cable Ties

Black Neutral

Sizes available from:

Diameter: **2.5mm** to **9mm** Length: **100mm** to **1030mm**

SELF ADHESIVE CABLE TIE HOLDERS ALSO AVAILABLE MASON MATE



RANGE AND RELIABILITY

ETA and CE approved products are available for next day delivery.

WOODSCREWS





Pozi Double Countersunk Twin Thread Woodscrew

Electro Brassed

Sizes available from:
Diameter: 4swg to 12swg
Length: 1/2" to 4"

Zinc Plated



Pozi Round Head Twin Thread Woodscrew

Zinc Plated

Sizes available from:

Diameter: 4swg to 10swg

Length: 1/2" to 3"



Pozi Countersunk Carcass Screw

Black Oxide
Sizes available from:
Diameter: 4mm
Length: 32mm & 45mm





Pozi Double Countersunk Single Thread Woodscrew

Zinc Plated

Sizes available from:
Diameter: 3mm to 6mm
Length: 12mm to 150mm



TIMBER

Pozi Double Countersunk Single Thread Woodscrew (Non-Ferrous)

A2 Stainless Steel
Sizes available from:
Diameter: 3mm to 6mm
Length: 12mm to 150mm

TIMBER MATE



Clutch Head Twin Thread Woodscrew

Zinc Plated

Sizes available from:
Diameter: 6swg to 12swg
Length: 3/4" to 2"

TIMBER



Slotted Round Brass Woodscrew

Self Colour
Sizes available from:
Diameter: 4swg to 8swg
Length: 1/2" to 1.1/2"

TIMBER. MATE



Slotted Countersunk Brass Woodscrew

Self Colour

Sizes available from:
Diameter: 2swg to 12swg
Lenath: 1/4" to 3"

TIMBER



Zinc Plated



Phillips Recess Bugle Head Drywall Screw

Phosphated
Sizes available from:
Diameter: 3.5mm & 4.2mm
Length: 25mm to 100mm



Phillips Recess Pan Head Drywall Screw

Zinc Plated

Sizes available from:
Diameter: 4.2mm

Length: 13mm



Phillips Recess Wafer Head Drywall Screw

Zinc Plated
Sizes available from:
Diameter: 4.2mm
Length: 13mm





Sizes available from:Diameter: **2.65mm**Length: **30mm** to **40mm**





RANGE AND RELIABILITY

The TimberMate® range is designed for the professional trades-person offering:

- Quality
- Reliability
- CE marking
- Value for money

COACHSCREWS





Hexagon Head Coachscrew

Zinc Plated Hot Dipped Galvanised **Sizes available from:** Diameter: **5mm** to **16mm**

Length: 20mm to 300mm



RANGE AND RELIABILITY



The full range of Mates products are available via the TradeFast website www.harclo.com Try it, its simple and it works!!

CAPS & COVERS



Surface Screw Cup

Solid Brass Brass Nickel Plated

Sizes available from: Diameter: 4G to 14G





Pozi Screw Cover Cup

Black Magnolia Teak White

Sizes available from:

C/W WASHER ALSO AVAILABLE TIMBER.



Turned Pattern Screw Cup

Solid Brass

Sizes available from: Diameter: **6G** to **12G**

TIMBER.

NAILS



Round Wire Nail

Bright - Self Colour Galvanised

Sizes available from: Length: 20mm to 150mm



Round Lost Nail

Bright - Self Colour Galvanised

Sizes available from: Length: 20mm to 150mm

> TIMBER. MATE



Length: **20mm** to **100mm**

TIMBER. MATE



Clout Head Nail

Galvanised

Sizes available from: Length: 20mm to 100mm

TIMBER.



Extra Large Head Clout Head Nail

Galvanised

Sizes available from: Length: 20mm to 100mm

TIMBER.



Brudaw Alloy Dowel

Zinc Plated

Sizes available from: Length: 3/4" to 3"

TIMBER MATE

THE TITE RANGE


RANGE AND RELIABILITY

THE TITE RANGE

























The award winning Tite®-Range is acknowledged as the most complete application specific offering on the market…but don't just take our word for it.

"It is simply very satisfying to have the work go well because you chose the best screw for the job - whether it be finish, head size or driving head." by Peter Brett/Tool Business

+ Hire magazine

RANGE AND RELIABILITY



STAINLESS STEEL RANGE



Hexagon Head Bolt A2 Stainless Steel Sizes available from: Diameter: M6 to M24 Length: 25mm to 150mm



DIN 931

METAL

METAL

DIN 7991

METAL

METAL

DIN 439B

Hexagon Head Setscrew A2 Stainless Steel A4 Stainless Steel Sizes available from: Diameter: M3 to M24 Length: 6mm to 200mm



Cup Square Hexagon Bolt & Nut A2 Stainless Steel Sizes available from: Diameter: M6 to M20 Length: 16mm to 400mm



DIN 603/555



All Thread A2 Stainless Steel A4 Stainless Steel Sizes available from: Diameter: M3 to M30 Lenath: 300mm to 3mtr



Hexagon Socket Cap Screw A2 Stainless Steel Sizes available from: Diameter: M2.5 to M416 Length: 6mm to 160mm



DIN 933

METAL

Hexagon Socket ISO: 7380 **Dome Screw** A2 Stainless Steel Sizes available from: Diameter: M3 to M12 Length: 6mm to 80mm **METAL**



Hexagon Socket Countersunk Screw

A2 Stainless Steel Sizes available from: Diameter: M3 to M16 Lenath: 6mm to 100mm



Hexagon Socket Setscrew

A2 Stainless Steel Sizes available from: Diameter: M3 to M12 Length: 2mm to 60mm



Hexagon Full Nut A2 Stainless Steel

A4 Stainless Steel Sizes available from: Diameter: M2 to M30

DIN 1587

DIN 934



Hexagon Lock Nut

A2 Stainless Steel Sizes available from: Diameter: M4 to M320



Hexagon Nylon Insert Nut Type T

A2 Stainless Steel A4 Stainless Steel Sizes available from: Diameter: M3 to M24

DIN 985

Hexagon Dome Nut

A2 Stainless Steel Sizes available from: Diameter: M4 to M20

METAL

BS 4320



Wing Nut

A2 Stainless Steel Sizes available from: Diameter: M5 to M16





Plain Washer Form A

A2 Stainless Steel A4 Stainless Steel

Sizes available from: Diameter: 3mm to 30mm



Plain Washer Form B

A2 Stainless Steel A4 Stainless Steel

Sizes available from: Diameter: 6mm to 24mm

METAL

METAI

METAL

DIN 125



Plain Washer Form C

BS 4320

METAL

METAL

METAL MATE

DIN 7985

DIN 963

A2 Stainless Steel Sizes available from: Diameter: 4mm to 20mm



Square Section Spring Washer

A2 Stainless Steel A4 Stainless Steel

Sizes available from: Diameter: 3mm to 24mm



Rectangular Section Spring Washer

A2 Stainless Steel

Sizes available from: Diameter: 5mm to 16mm



DIN 127B





Internal Shakeproof Washer

A2 Stainless Steel

Sizes available from: Diameter: 4mm to 24mm



Crinkle Washer

A2 Stainless Steel

Sizes available from: Diameter: 4mm to 12mm



DIN 965





Slotted Pan Head Machine Screw

A2 Stainless Steel

Sizes available from: Diameter: M3 to M8 Length: **56mm** to **80mm**



METAL

DIN 7980

METAL

DIN 6798

Pozi Countersunk Machine Screw

A2 Stainless Steel

Sizes available from: Diameter: M3 to M8 Length: 5mm to 50mm



DIN 7981

Pozi Pan Head Machine Screw A2 Stainless Steel





Pozi Countersunk Self Tapping Screw (AB)

A2 Stainless Steel

Sizes available from: Diameter: 4swg to 14swg Lenath: 3/8" to 2"



METAL

METAL

Tapping Screw (AB) A2 Stainless Steel

Sizes available from: Diameter: 4swg to 14swg Length: 1/4" to 2"

Pozi Pan Head Self



Dome Rivet



Sizes available from: Diameter: 3.0mm to 6.4mm



Countersunk Rivet Stainless Steel

Sizes available from: Diameter: 3.2mm to 4.8mm



Dome Head Rivet Nut

A2 Stainless Steel

Sizes available from: Diameter: M4 to M8

SARIV

Dome Head Standard low-profile head, suitable for most applications.

SARIV

120° head design. Used wherever a flush surface is required.

SARIV

29



Terry Hose Clips

Stainless Steel

Sizes available from: 8mm to 140mm



Jubilee Hose Clips

Stainless Steel Sizes available from: 9.5mm to 318mm



ETA Approved Through Bolt

A4 Stainless Steel

Sizes available from: Diameter: M8 to M20 Length: 60mm to 220mm



MI

TERRY



A4 Stainless Steel Sizes available from: Diameter: 6mm to 20mm Length: 18mm to 151mm



Plain Drop In Wedge Anchor

A4 Stainless Steel Sizes available from: Diameter: M6 to M16



Studs

A2 Stainless Steel

Sizes available from: Diameter: M8 to M20 Length: 110mm to 260mm





Internal Threaded Sockets

A2 Stainless Steel Sizes available from: Diameter: M8 to M16



Hammer Fixing

Nvlon - Stainless Steel Screw Sizes available from: Diameter: 6mm to 8mm Length: 40mm to 100mm



Pozi Double Countersunk Single Thread Woodscrew

A2 Stainless Steel

Sizes available from: Diameter: 3mm to 5mm Length: 12mm to 100mm









Tongue & Groove Screw

Net-Coat® Clear - Stainless 316 Sizes available from:



MASON

Tongue

RANGE AND RELIABILITY

Stainless Steel: A pleasantly surprising range...at reassuring prices. All available next day.





Diameter: 3.5mm Length: 32mm to 49mm



BRASS RANGE



Hexagon Head Setscrew

DIN 933

DIN 439B

Sizes available from: Diameter: M4 to M16 Length: 10mm to 75mm



All Thread

Sizes available from: Diameter: M4 to M20 Length: 1mtr

Sizes available from:

Diameter: 3mm to 20mm



Hexagon Full Nut

DIN 934

Sizes available from: Diameter: M2.5 to M24



BS 4320

Hexagon Lock Nut



Sizes available from: Diameter: M4 to M20



Plain Washer Form A

DIN 125

METAL MATE



Sizes available from: Diameter: 6mm to 20mm

Plain Washer Form B

METAL

DIN 84

METAL

TIMBER

MATE

METAL

Slotted Countersunk Machine Screw

Sizes available from: Diameter: M3 to M8 Length: 6mm to 50mm



Slotted Pan Head Machine Screw

Sizes available from: Diameter: M3 to M6 Length: 6mm to 50mm **DIN 85**

METAL

Slotted Cheese Machine Screw

Sizes available from: Diameter: M3 to M6 Length: 6mm to 30mm

Slotted Round Brass Woodscrews

Self Colour

Sizes available from: Diameter: 4swg to 8swg Length: 1/2" to 1.1/2"



Slotted Countersunk Brass Woodscrews

Self Colour

Sizes available from: Diameter: 2swg to 12swg Length: 1/4" to 3"

TIMBER

Surface Screw Cup

Solid Brass

Sizes available from: Diameter: 4G to 14G

Turned Pattern Screw Cup



Sizes available from: Diameter: 6G to 12G



RANGE AND RELIABILITY



The Mates brass range: as good a range as the non-ferrous 'specialists' offering are.



NYLON RANGE



Hexagon Head Setscrew

DIN 933

Nylon Sizes available from:

Diameter: M5 to M16 Length: 16mm to 55mm



All Thread

Mild Steel All Thread

Sizes available from: Diameter: M6 to M12 Length: 1mtr



Hexagon Full Nut

DIN 934

Sizes available from: Diameter: M3 to M12



METAL

METAL

Plain Washer Form A

DIN 125

Sizes available from:

Diameter: 2.5mm to 24mm



Frame Fixing

Nylon - Zinc & Yellow Screw Sizes available from:

Diameter: 8mm & 10mm Length: 60mm to 160mm



MASON MATE

METAL



Nvlon - Stainless Steel Screw Sizes available from:

Diameter: 5mm to 8mm Length: 30mm to 135mm

MASON



Window Frame Anchor

Nvlon / Steel

Sizes available from:

Diameter: 8mm & 10mm Length: 75mm to 165mm



Plasterboard Fixings

Sizes available from:

Diameter: **4.5mm**

Length: 30mm to 45mm



Plastic Wall Plugs

Colours available in: Brown: 7mm x 37mm

Red: 6mm x 30mm Yellow: 5mm x 25mm

TIMBER





Sizes available from: Diameter: 5mm to 14mm Lenath: 25mm to 75mm

TIMBER



Cable Ties

Black

Neutral

Sizes available from:

Diameter: 2.5mm to 9mm

Length: 100mm to 1030mm

SELF ADHESIVE CABLE TIE HOLDERS ALSO AVAILABLE

TIMBER

Pozi Screw Cover Cup Black



Magnolia Teak White

Sizes available from:

Diameter: 6G to 14G

TIMBER

RANGE AND RELIABILITY



The Mates range: more than just carbon steel fasteners.





TIMBER.





CERTIFIED RANGE RANGE AND RELIABILITY

CERTIFIED RANGE



Hexagon Head Bolt 8.8

Self Colour Zinc Plated Hot Dipped Galvanised Sizes available from: Diameter: M4 to M56 Length: 8mm to 600mm



Hexagon Head Bolt 8.8 Fine Pitch

Self Colour Sizes available from: Diameter: M10 to M24 Length: 40mm to 200mm



DIN 960

Hexagon Head Bolt 10.9

Self Colour Zinc Plated Sizes available from: Diameter: M6 to M56 Length: 30mm to 760mm



DIN 931

METAI





Hexagon Head Setscrew 8.8 Fine Pitch

Self Colour Sizes available from: Diameter: M8 to M24 Length: 16mm to 100mm



METAL

Hexagon Head Setscrew 10.9 DIN 933 Self Colour

Zinc Plated Sizes available from:

Diameter: M5 to M36 Lenath: 10mm to 200mm



UNC / UNF / BSW / BSF SIZING ALSO AVAILABLE



Self Colour Zinc Plated Sizes available from: Diameter: M2 to M48 Lenath: 4mm to 400mm

Cap Screw 12.9



DIN 912

METAL MATE

Hexagon Socket Dome Screw 10.9

Self Colour Zinc Plated Sizes available from: Diameter: M3 to M16 Lenath: 5mm to 120mm



ISO: 7380

METAL MATE

DIN 603/555

Hexagon Socket Countersunk Screw 10.9

Self Colour Zinc Plated

05

Sizes available from: Diameter: M3 to M24 Lenath: 6mm to 200mm



DIN 7991

Assembled Bolting 8.8 EN: 15048-1:2007

7inc Plated Hot Dipped Galvanised Sizes available from: Diameter: M12 to M24 Length: 30mm to 90mm



METAI

Cup Square Hexagon Bolt & Nut 4.8

Zinc Plated Hot Dipped Galvanised Sizes available from: Diameter: M6 to M20 Length: 16mm to 400mm





METAL

Pozi Double Countersunk Twin Thread Woodscrew

Zinc Plated Electro Brassed Sizes available from: Diameter: 4swg to 12swg Length: 1/2" to 4"



Pozi Round Head Twin Thread Woodscrew

Zinc Plated Sizes available from: Diameter: 4swg to 10swg Lenath: 1/2" to 3"



TIMBER

Pozi Countersunk Carcass Screw

Black Oxide Sizes available from: Diameter: 4mm Length: 32mm & 45mm



Pozi Double Countersunk Single Thread Woodscrew

Zinc Plated Sizes available from: Diameter: 3mm to 6mm Length: 12mm to 150mm



TIMBER



TIMBER



Phillips Recess Bugle Head Drywall Screws

Zinc Plated Phosphated Sizes available from: Diameter: 3.5mm & 4.2mm Length: 25mm to 100mm



Phillips Recess Pan Head Drywall Screws

Zinc Plated Sizes available from: Diameter: 4.2mm Length: 13mm



Phillips Recess Wafer Head Drywall Screws

Zinc Plated Sizes available from: Diameter: 4.2mm Length: 13mm





Hexagon Head Coachscrew

Zinc Plated Hot Dipped Galvanised Sizes available from: Diameter: 5mm to 16mm Length: 20mm to 300mm



TIMBER

Deck-Tite Deck & Outdoor Screw

Net-Coat® Green Sizes available from: Diameter: 4.5mm Lenath: 25mm to 63mm



Deck-Tite Plus

Deck & Outdoor Screw

Net-Coat® Clear - Stainless 316 Sizes available from: Diameter: 4.5mm Lenath: 50mm to 75mm







Timber-Tite

Heavy Duty Timber Screw

Net-Coat® Green Sizes available from: Diameter: 6.5mm



Fite®

Screw-Tite

All Purpose Screw

Net-Coat® Yellow Sizes available from: Diameter: 3mm to 6mm Lenath: 12mm to 150mm



Fite*

Lenath: 45mm Screw





Tonque-Tite

Tongue & Groove Screw

Net-Coat® Clear - Stainless 316 Sizes available from: Diameter: 3.5mm Length: 32mm to 49mm



Tongue

Floor-Tite

Flooring Screw

Net-Coat® Blue Sizes available from: Diameter: 4.2mm Length: **45mm** & **55mm**





Lost-Tite

Discreet Fix Screw

Net-Coat® Yellow Extra Sizes available from: Diameter: 3.5mm Length: 25mm to 49mm







Hinge-Tite

Hinge Screw Net-Coat® Brass

Net-Coat® Chrome Sizes available from: Diameter: 4mm & 4.5mm Length: 25mm to 40mm



ETA Approved Through Bolt

Zinc Plated

Sizes available from: Diameter: M8 to M20 Length: 60mm to 220mm



ETA Approved Through Bolt (Alloy)

A4 Stainless Steel Sizes available from: Diameter: M8 to M20 Length: 60mm to 220mm







NDEX



ETA Approved Countersunk Heavy Duty Anchor

Zinc Plated Sizes available from: Diameter: 6mm to 12mm Length: 10mm to 40mm



ETA Approved Heavy Duty Anchor Hexagon Bolt

Zinc Plated

Sizes available from: Diameter: 12mm to 28mm Length: **80mm** to **185mm**



Zinc Plated

ETA Approved Heavy Duty Anchor Stud

Sizes available from: Diameter: 8mm to 16mm Length: **10mm** to **70mm**







Styrene Free Polyester Resin

Sizes available: Size: 165ml & 300ml



Styrene Free Epoxy Acrylate Sizes available:

Size: 410ml



High-Load Vinylester Resin

Sizes available:



Hexagon Full Nut Grade 10




ETA Approved Spin In Capsules

Vinylester Sizes available from: Diameter: 8mm to 20mm



MASON MATE





DIN 934



Sizes available from:

Self Colour

Zinc Plated



DIN 934









TECHNICAL INFORMATION

wasn	ner Dir		ension MPERIA		hart		_			MI	ETRIC					ВА	
	Bright Black				Bright					Black			BA				
INS	T3 T L.P H		T4 L.P	T4 H.P	Т8	Т7	мм	A H.P	B L.P	C H.P	D L.P	E	F	G	B.A.	T1	T2
3/32			5/16	5/16			2	5.0							0	.500	.625
1/8	5/16 5/	16	3/8	3/8			2.5	6.0							1	.443	.565
5/32	3/8 3/	/8 ₁₈	7/16	7/16			3	7.0							2	.391	
3/16	7/16 7/	16	1/2	1/2		1/2	4	9.0		10.0					3	.341	
1/4	9/16 9/	16	5/8	5/8	3/4	5/8	5	10.0	10.0	12.5		10.0		15.0	4	.301	.378
5/16	5/8 5/	′8 ₁₅	3/4	3/4	7/8	3/4	6	12.5	12.5	14	14	12.5		18	5	.268	.335
3/8	3/4 3/	4 ₁₅	7/8	7/8	1"	7/8	7	14							6	.233	.288
7/16	7/8 7/	′8 ₁₃	1″	1"	1.1/8		8	17	17	21	21	17	21	24	7	.208	.257
1/2	1″ 1	"	1.1/8	1.1/8	1.1/4	1.1/8	10	21	21	24	24	21	24	30	8	.185	.228
9/16	1.1/8 1.1	/8	1.1/4	1.1/4	1.3/8	1.1/4	12	24	24	28	28	24	28	36	10		.176
5/8	1.1/4 1.1	/4	1.3/8	1.3/8	1.1/2	1.3/8	14	28	28	30	30	28	30	42			
3/4	1.1/2 1.1	/2	1.5/8	1.5/8	1.3/4	1.5/8	16	30	30	34	34	30	34	48		Gauge	es
7/8	1.5/8 1.5	5/8	1.7/8	1.7/8	2"	1.7/8	18	34	34	37	37	34	37	54		S.W.G	ī.
1″	1.7/8 1.7	7/8	2.1/8	2.1/8	2.1/4	2.1/8	20	37	37	39	39	37	39	60	No.	INS	MM
1.1/8	2.1/8 2.1	/8	2.3/8	2.3/8	2.1/2	2.3/8	22	39	39			39	44	66	25 24	.020 .022	0.50 0.55
1.1/4	2.3/8 2.3	3/8	2.5/8	2.5/8	2.3/4	2.5/8	24	44	44	50	50	44	50	72	23 22	.024	0.60 0.70
1.3/8	2.5/8 2.5	5/8	2.7/8	2.7/8	3"	2.7/8	27	50				50			21 20	.032 .036	0.80 0.90
1.1/2	2.7/8 2.7	7/8	3.1/8	3.1/8	3.1/4	3.1/8	30	56	56 _{2.5}			56			19 18	.040 .048	1.01 1.21
1.5/8					3.1/2	3.3/8	33	60	60			60	66	99	17 16	.056 .064	1.42 1.62
1.3/4	3.3/8 3.3	3/8	3.5/8	3.5/8	3.3/4	3.5/8	36	66	66			66	72 5.0	108	15 14	.072 .080	1.82 2.02
2"	3.5/8 3.5	5/8	4.1/8	4.1/8	4.1/4	4.1/8	39	72	72			72	77	117	13 12	.092 .104	2.33 2.63
							42					77	78		11 10	.116 .128	2.93 3.24
							48					92	92 _{8.0}		9 8	.144 .160	3.64 4.05
							56					105			7 6	.176 .192	4.45 4.90
							64					115			5	.212	5.36

Equival	<u>lents</u>					
M2	5/64"	No. 4	2.9mm		30mm	1.1/4"
М3	1/8"	No. 6	3.5mm		40mm	1.1/2"
M4	5/32"	No. 8	4.2mm		50mm	2"
M5	3/16"	No. 10	4.8mm		65mm	2.1/2"
M6	1/4"	No. 12	5.5mm		75mm	3"
M8	5/16"	No. 14	6.3mm		90mm	3.1/2"
M10	3/8"	No. 16	7.0mm		100mm	4"
M12	1/2"				125mm	5"
M14	9/16"	1ft = 12" =			150mm	6"
M16	5/8"	2ft = 24" =		֓֟֟֝֟֝֟֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓		
M18	11/16"	3ft = 36" =	900mm		10BA = 1/16 = 1.5mm	
M20	3/4"	6ft = 72" =	1800mm		8BA = 3/32 = 2.5mm	
M22	7/8"	10ft = 120"	= 3000mm]	6BA = 1/8 = 3.0mm	
M24	1"				4BA = 9/64	= 3.5mm
M27	1.1/8"				2BA = 3/16	= 5.0mm
M30	1.1/4"				0BA = 1/4 =	6.0mm

Standard Thread Lengths

Cup Square Hexagon

Up to & including 150mm length will be T.T.H.

(threaded to head)

Above 150cm long = 150mm of thread

e.g. M10 x 160mm cup square hexagon will have 10mm of plain shank.

Socket Dome Screws

Grade 10.9 will be T.T.H.

(threaded to head)

For Socket Cap and Socket Countersunk

Please see manufacturers specifications.

DIN 931 Hexagon Head Bolts

Metric up to 120mm long = 2 x dia + 6mm

e.g. M10 x 75 will have 26mm of thread!

 $2 \times 10mm = 20mm + 6mm = 26mm$

125mm - 200mm long = $2 \times dia + 12mm$ Over 200mm long = $2 \times dia + 25mm$

<u>High Tensile Head Diameter & Torque Information</u>

Product No.	Material	Grade Bolts & Set Screws	Thread	Diameter Bolts, Set Screws & Hex Nuts	Standard No. Bolts & Set Screws	Pitch / TPI Bolts, Set Screws & Hex Nuts	Across Flats Bolts, Set Screws & Hex Nuts	Tightening Torque (Self Colour)	Tightening Torque (Zinc Plated)
0318M	High Tensile	8.8	Metric	M4	DIN 933	0.70 PITCH	7mm A/F	3.4Nm	2.5Nm
0317M	High Tensile	8.8	Metric	M5	DIN 931/933	0.80 PITCH	8mm A/F	6.9Nm	5.175Nm
0317M	High Tensile	8.8	Metric	M6	DIN 931/933	1.00 PITCH	10mm A/F	11.7Nm	8.77Nm
0317M	High Tensile	8.8	Metric	M8	DIN 931/933	1.25 PITCH	13mm A/F	28Nm	21Nm
0317M	High Tensile	8.8	Metric	M10	DIN 931/933	1.50 PITCH	17mm A/F	56Nm	42Nm
0317M	High Tensile	8.8	Metric	M12	DIN 931/933	1.75 PITCH	19mm A/F	98Nm	73.5Nm
0317M	High Tensile	8.8	Metric	M14	DIN 931/933	2.00 PITCH	22mm A/F	141Nm	105Nm
0317M	High Tensile	8.8	Metric	M16	DIN 931/933	2.00 PITCH	24mm A/F	244Nm	183Nm
0317M	High Tensile	8.8	Metric	M18	DIN 931/933	2.50 PITCH	27mm A/F	295Nm	221Nm
0317M	High Tensile	8.8	Metric	M20	DIN 931/933	2.50 PITCH	30mm A/F	476Nm	357Nm
0317M	High Tensile	8.8	Metric	M22	DIN 931/933	2.50 PITCH	32mm A/F	570Nm	455Nm
0317M	High Tensile	8.8	Metric	M24	DIN 931/933	3.00 PITCH	36mm A/F	822Nm	616.5Nm
0317M	High Tensile	8.8	Metric	M27	DIN 931/933	3.00 PITCH	41mm A/F	980Nm	735Nm
0317M	High Tensile	8.8	Metric	M30	DIN 931/933	3.50 PITCH	46mm A/F	1,633Nm	1,225Nm
0317M	High Tensile	8.8	Metric	M33	DIN 931/933	3.50 PITCH	50mm A/F	1,970Nm	1,570Nm
0317M	High Tensile	8.8	Metric	M36	DIN 931/933	4.00 PITCH	55mm A/F	2,854Nm	2,141Nm

<u>Pozidriv Screwdriver Point Size</u> <u>and Screw Gauge Combination</u>

Screwdriver Point Size	Woodscrew Gauge
1	2 to 4
2	5 to 10
3	12 to 14
4	16+

Stainless Steel Grading

A2 - 18/8 - 302 Stainless Steel

A4 - 18/10/3 - 316 Stainless Steel

Grade 70 = 700 Newtons/mm² = Grade 7.7 approx

Grade 80 = 800 Newtons/mm² = Grade 8.8 approx

Thread Data

Nominal Size

1/4"

5/16"

3/8"

7/16"

1/2"

9/16"

5/8"

3/4"

7/8"

1"

1.1/8"

1.1/4"

1.3/8"

1.1/2"

1.3/4"

2"

2.1/4"

2.1/2"

2.3/4"

3"

3.1/4"

3.1/2"

4"

4.1/2"

5"

5.1/2"

6"

No. of threads	per	inch
----------------	-----	------

B.S.W

20

18

16

14

12

12

11

10

9

8

7

7

6

6

5

4.5

4

4

3.5

3.5

3.25

3.25

3

2.875

2.75

2.75

2.5

hrea	ds per inch	
	B.S.F	
	26	
	22	
	20	
	18	
	16	
	16	
	14	
	12	
	11	
	10	
	9	
	9	
	8	
	8	
	7	
	7	
	6	
	6	
	6	
	5	
	5	
	4.5	
	4.5	
	-	
	-	
	-	
		1

No. of threads per inch

Nominal Size	U.N.C	U.N.F
1/4"	20	28
5/16"	18	24
3/8"	16	24
7/16"	14	20
1/2"	13	20
9/16"	12	18
5/8"	11	18
3/4"	10	16
7/8"	9	14
1″	8	12
1.1/8"	7	12
1.1/4"	7	12
1.3/8"	6	12
1.1/2"	6	12
1.3/4"	5	-
2"	4.5	-
2.1/4"	4.5	-
2.1/2"	4	-
2.3/4"	4	-
3″	4	-
3.1/4"	4	-
3.1/2"	4	-
4"	4	-

Thread Pitch

Metric	Course	Fine	Extra Fine
M3	0.50	-	-
M4	0.70	-	-
M5	0.80	-	-
M6	1.00	-	-
M8	1.25	1.00	-
M10	1.50	1.25	1.00
M12	1.75	1.50	1.25
M14	2.00	1.50	-
M16	2.00	1.50	-
M18	2.50	2.00	1.50
M20	2.50	2.00	1.50
M22	2.50	2.00	1.50
M24	3.00	2.00	1.50
M27	3.00	2.00	1.50
M30	3.50	2.00	1.50
M33	3.50	2.00	1.50
M36	4.00	3.00	1.50
M39	4.00	3.00	1.50
M42	4.50	3.00	1.50
M45	4.50	3.00	1.50
M48	5.00	3.00	1.50
M52	5.00	3.00	1.50
M56	5.50	4.00	2.00
M60	5.50	4.00	2.00
M64	6.00	4.00	2.00
M68	6.00	4.00	2.00
M72	6.00	4.00	2.00
M76	6.00	4.00	2.00
M80	6.00	4.00	2.00
M85	6.00	4.00	2.00
M90	6.00	4.00	2.00
M100	6.00	4.00	2.00

Hexagon Drive Sizes For Socket Cap Screws

Category	Grade	Standard	Diameter	Wrench Key
Skt Cap Screw	12.9	DIN 912	M2	1.5mm
Skt Cap Screw	12.9	DIN 912	M2.5	2mm
Skt Cap Screw	12.9	DIN 912	M3	2.5mm
Skt Cap Screw	12.9	DIN 912	M4	3mm
Skt Cap Screw	12.9	DIN 912	M5	4mm
Skt Cap Screw	12.9	DIN 912	M6	5mm
Skt Cap Screw	12.9	DIN 912	M8	6mm
Skt Cap Screw	12.9	DIN 912	M10	8mm
Skt Cap Screw	12.9	DIN 912	M12	10mm
Skt Cap Screw	12.9	DIN 912	M14	12mm
Skt Cap Screw	12.9	DIN 912	M16	14mm
Skt Cap Screw	12.9	DIN 912	M20	17mm
Skt Cap Screw	12.9	DIN 912	M24	19mm
Skt Cap Screw	12.9	DIN 912	M30	22mm
Skt Cap Screw	12.9	DIN 912	M36	27mm

<u>Hexagon Drive Sizes For Socket Dome (Button) Screws</u>

Category	Grade	Standard	Diameter	Wrench Key
Skt Dome Screw	10.9	ISO 7380	M3	2mm
Skt Dome Screw	10.9	ISO 7380	M4	2.5mm
Skt Dome Screw	10.9	ISO 7380	M5	3mm
Skt Dome Screw	10.9	ISO 7380	M6	4mm
Skt Dome Screw	10.9	ISO 7380	M8	5mm
Skt Dome Screw	10.9	ISO 7380	M10	6mm
Skt Dome Screw	10.9	ISO 7380	M12	8mm
Skt Dome Screw	10.9	ISO 7380	M16	10mm

Hexagon Drive Sizes For Socket Countersunk Screws

Category	Grade	Standard	Diameter	Wrench Key
Skt CSK Screw (90° Head)	10.9	DIN 7991	M3	2mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M4	2.5mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M5	3mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M6	4mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M8	5mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M10	6mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M12	8mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M16	10mm
Skt CSK Screw (90° Head)	10.9	DIN 7991	M20	12mm

Hexagon Drive Sizes For Socket Set (*Grub***) Screws**

Category	Grade	Standard	Diameter	Wrench Key
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M2	1mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M2.5	1.2mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M3	1.4mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M4	2mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M5	2.5mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M6	3mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M8	5mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M10	6mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M12	8mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M16	10mm
Skt Setscrew (Plain Cup Point)	14.9	DIN 916	M20	14mm

Electro Chemically Induced Corrosion

Many corrosion problems arise from the fact that two dissimilar metals are in contact, leading to electro-chemical activity in damp conditions. This can be reduced or eliminated by controlling the embience (e.g. particularly limiting the humidity), or isolating dissimilar metals by insulating compounds, washers, etc. Further protection can be given by applying coatings of grease, paint, waxes, etc.

Compatibility Table - Metal-to-Metal Contact

	Aluminium	Aluminium Bronze	Cast Iron	Copper	Manganese Bronze	Mild Steel	Stainless Steel	Phosphor Bronze
Aluminium	•	×	×	×	×	×	•	×
Aluminium Bronze	×	•	×	•	0	×	(•
Cast Iron	×	×	•	×	×	•	×	×
Copper	×	•	×	•	0	×	0	•
Manganese Bronze	×	0	×	0	•	×	0	0
Mild Steel	×	×	•	×	×	•	×	×
Stainless Steel	•	0	×	0	0	×	•	0
Phosphor Bronze	×	•	×	•	0	×	0	•

- Can be used together under all conditions
- Only safe to use together in dry conditions
- Limited compatibility may or may not prove suitable under all conditions
- × Not compatible should not be used together under any condition

Operating Temperature Range

All Temperature in degrees centigrade (°C). Black Mild Steel

	Minimum	Maximum
Whit Threads	-50°	+300°
Metric - Grade 4.6	-50°	+300°
Metric - Grade 5.6	-50°	+300°
Metric - Grade 6.8	-50°	+300°

High Tensile

	Minimum	Maximum
Whit & BSF - Grade R	-50°	+300°
UNC & UNF - Grade S	-50°	+300°
Metric - Grade 8.8	-50°	+300°
Metric - Grade 10.9	-50°	+300°

Nylon 66

	Minimum	Maximum
Metric	-70°	+255°

Stainless Steel

	Minimum	Maximum
18/8 - A2 - 302 Quality	-250°	+575°
18/10/3 - A4 - 316 Quality	-250°	-
Stress Relaxation Occurs	-	+600°
Oxidisation Resistance Up To	-	+800°

Socket Products - Grade 12.9

	Minimum	Maximum
All Standard Products In Self Colour Finish	-50°	+300°
Austenitic Stainless Products	-50°	+430°



mm	20	25	30	40	45	50	60	65	75	90	100	125	150
1.60	2710	2120	-	-	-	-	-	-	-	-	-	1	1
1.80	1	1720	-	-	-	-	-	-	-	-	-	1	1
2.00	-	1430	1170	970	-	-	-	-	-	-	-	-	-
2.36	-	-	840	750	640	550	-	-	-	-	-	-	-
2.65	-	-	-	-	575	440	385	350	-	-	-	-	-
3.00	-	-	-	-	-	340	310	275	-	-	-	-	-
3.35	-	-	-	-	-	-	255	230	194	-	-	-	-
3.75	-	-	-	-	-	-	-	-	154	-	-	-	-
4.00	-	-	-	-	-	-	-	-	121	106	68	-	-
4.50	-	-	-	-	-	-	-	-	-	-	77	-	-
5.00	-	-	-	-	-	-	-	-	-	-	66	53	-
5.60	-	-	-	-	-	-	-	-	-	-	-	42	-
6.00	-	-	-	-	-	-	-	-	-	-	-	-	29

Lost Head Nails per kilo

mm	40	50	60	65	70	
2.36	760	-	-	-	-	
2.65	-	420	-	-	-	
3.00	-	360	330	270	-	
3.35	-	-	270	240	-	
3.75	-	-	-	-	160	

Annular Ring Nails per kilo

mm	20	25	30	40	45	50	65	75	100
2.00	1900	1430	-	-	-	-	-	-	-
2.36	-	-	840	750	-	-	-	-	-
2.65	-	-	-	575	510	440	-	-	-
3.00	-	-	-	-	-	340	-	-	-
3.35	-	-	-	-	-	290	230	-	-
3.75	-	-	-	-	-	-	-	154	110
5.00	-	-	1	-	-	-	-	-	32

20	25	30	40	45	50	65	75	100
1900	1430	-	-	-	-	-	-	-
-	-	840	750	-	-	-	-	-
-	-	-	575	510	440	-	-	-
-	-	-	-	-	340	-	-	-
-	-	-	-	-	290	230	-	-
-	-	-	-	-	-	-	154	110
-	-	-	-	-	-	-	-	32
	1900 - - - - -	1900 1430	1900 1430 840	1900 1430 840 750 - 575	1900 1430	1900 1430 - - - - - - 840 750 - - - - - 575 510 440 - - - - 340 - - - - 290 - - - - -	1900 1430 - </th <th>1900 1430 - - - - - - - - 840 750 - - - - - - - 575 510 440 - - - - - - 340 - - - - - - 290 230 - - - - - - 154</th>	1900 1430 - - - - - - - - 840 750 - - - - - - - 575 510 440 - - - - - - 340 - - - - - - 290 230 - - - - - - 154



Nail Kilo Count

Galvanised Clout Nails per kilo

mm	20	25	30	40	50	65	75	100
2.36	-	-	832	698	-	-	-	-
2.65	1035	815	661	570	432	-	-	-
3.00	-	-	540	-	-	-	-	-
3.35	-	-	-	350	290	-	-	-
3.75	-	-	-	-	-	182	150	-
4.50	-	-	-	-	-	-	-	75

E.L.H. Clout Nails per kilo

mm	15	20	25	30	40	50
2.36	650	580	485	600	478	334

Galv Spring Head & Slab Nails per kilo

mm	65 Spring	100 Slab
3.35	140	100

Galvanised Staples per kilo

mm	15	20	25	30	40	45	50
1.60	2191	-	-	-	-	-	-
2.00	-	1079	-	-	-	-	-
2.65	-	-	486	-	-	-	-
3.35	-	-	290			-	-
3.55	-	-	-	240	-	-	-
4.00	-	-	-	-	136	110	-
5.00	-	-	-	-	-	-	106

Copper Nails per kilo

mm	25	30	38	45	50	65	
2.36	-	748	-	-	-	-	
2.65	740	560	460	400	327	-	
3.00	-	470	398	366	276	-	
3.35	440	376	335	308	241	195	
4.00	-	-	-	-	-	140	

Jagged Plasterboard Nails per kilo

mm	30	40	50
2.65	700	570	422

Panel Pins per kilo

mm	15	20	25	30	40	50	
1.25	6400	-	-	-	-	-	
1.40	-	3970	2090	-	-	-	
1.60	-	3140	2340	1900	1590	-	
2.00	-	-	-	-	-	770	

Aluminium Nails per kilo

mm	25	30	38	50	60	65	70	75
2.65	-	1848	1596	-	-	-	-	-
3.00	-	-	-	-	-	-	-	-
3.35	1540	-	980	812	680	640	590	530

Oval Nails per kilo

mm	25	30	40	50	65	75	100	125	150
	2253	1480	940	470	230	125	64	44	31

Floor Brads per kilo Cut Nails per kilo

Length	Qty
40	616
50	286
60	202
65	175
75	103
90	66
100	48
125	30
150	19
175	13
200	11

Galvanised Drive Screw per kilo

mm	50	60	65	70	75	80	90	100	115	120	125	140	150	175
14G (5.4mm)	91	71	70	70	64	61	53	47	43	40	39	37	-	-
16G (6.4mm)	-	-	-	-	-	-	-	34	30	-	28	-	23	-
18G (7.4mm)	-	-	-	-	-	-	-	28	26	-	23	21	19	17

FIXINGS SELECTION CHART _____

	PRODUCTS STATE	Concrete	Concrete Blocks	Hollow Blocks	Solid Brick	Perforated Brick	Aerated Concrete	Stone	Plasterboard	ETA Approved
	Through Bolts	•								
	ETA Approved Through Bolts	•								•
	Heavy Duty Anchors	•								•
	Sleeve Anchors	•	•		•	0		•		
	Shield Anchors	•	•		•			•		
	Drop In Anchors	•			0			0		
hirinin	Screwbolts	•	•	•	•	•		•		
	Styrene Free Polyester Resin	•	•	•	•	•	•	•		•
	Styrene Free Epoxy Acrylate	•	•	•	0	0	0	0		•
	High-Load Vinylester Resin	•	•	•	0	0	0	0		•
140	Spin In Capsules	•								•
	Hammer In Capsules	•								
	Frame Fixings	•	•		•	0	0	•		
-	Hammer Fixings	•	•		•	0		•		
	Window Frame Anchors	•	•		•			0		
	Concrete Screws	•	•	•	•	•		•		
	Hollow Wall Anchors			•					•	
(1,0,0,0,	Plasterboard Fixings								•	
4	Spring Toggles			•					•	
-	Nylon Wall Plugs	•	•	•	•	•	•	•		
	KEY Suita	ble •	Mo	ore S	uital	ble F	ixing	gs Av	/aila	ble o



Harrison & Clough Ltd Harclo Road Keighley West Yorkshire BD21 4DW

Tel: +44 (0) 844 571 22 22 Fax: +44 (0) 844 571 22 33

www.harclo.com

